

OMEGA Compressors

Quality Compressed Air Products

2 year warranty



Contractor Series



DP-2004V



DP-2022H



PUK-2008MDC



PUK-5520G



PUK-5508G



PUK-9008G



TUE-8008GE

- Direct Drive Units have splash lubricated pump with cast iron sleeve for longer life
- Belt Drive Units have durable cast iron pumps
- Splash type lubrication
- All cast iron pumps have steel valves for longer life
- Flywheels designed for excellent pump cooling
- Manual reset for overload protection
- Dual control-start/stop with pressure switch or constant speed operation for electric belt drive unit
- All gas units equipped with Honda Gas Engines
- Idle-down throttle control for gas belt drive unit
- All units are factory tested prior to shipment
- For farms and professional contractors

Specifications

MODEL	PEAK HP	RUNNING HP@90 PSI	ACTUAL 90 PSI	FAD-CFM 125 PSI	MAX. PSI	VOLTAGE/ PHASE	TANK SIZE	NOISE LEVEL DBA	AMP DRAW @ 125 PSI	PUMP RPM	WEIGHT LBS.	REMARKS
DP-2004V	2	1.5	6	4.6	125	115V/1 PH	3.2	83	12	3450	70	PAN-CAKE
DP-2022H	2	1.5	6	4.6	125	115V/1 PH	4	83	12	3450	80	TWIN-STACK
PUK-2008MDC	2	2	9.5	8	125	115V/1 PH	8	70	22	900	200	TWIN-TANK
PUK-5508G	5.5	5.5	12.5	10.5	125	5.5 HP GAS	8	90 RUN/82 IDLE	N/A	1100	185	TWIN-TANK
PUK-5520G	5.5	5.5	12.5	10.5	125	5.5 HP GAS	20	90 RUN/82 IDLE	N/A	1100	200	20 GAL. PORTABLE
PUK-9008G	9	9	20.6	17.6	125	9 HP GAS	8	90 RUN/82 IDLE	N/A	1100	225	TWIN-TANK
MODEL	PEAK HP	RUNNING HP@140 PSI	ACTUAL 140 PSI	FAD-CFM 175 PSI	MAX. PSI	VOLTAGE/ PHASE	TANK SIZE	NOISE LEVEL DBA	AMP DRAW @ 125 PSI	PUMP RPM	WEIGHT LBS.	REMARKS
TUE-8008GE	8	8	15.6	12.5	175	8 HP GAS	8	90 RUN/82 IDLE	N/A	1100	225	ELECTRIC START